



Rubber Track Carriers

# Terramac 9T

## Unit Specifications and Dimensions

DIMENSIONS	
Full Length	5.4 m
Full Width	2.6 m
Wheel Base	3.9 m
Min Ground Clearance	.51 m
Front Overhang	.46 m
Track Width	.68 m
Track Length	9.8 m
Full Height	2.8 m
Height of Dump Bed	1.2 m
Height of Dump Side	.4 m
Length of Dump Bed	3.7 m
Width of Dump Bed	2.5 m
Dumping Angle	60°
Machine Weight (no bed)	6,803 kg

ENGINE	
Manufacturer	Cummins
Model	QSB 6.7
Displacement	6.7 l
Horsepower	172 kW
Electrical System	12 VDC
Battery	8D with 1500 CCA
Fuel Capacity	160 l



HYDRAULICS	
Transmission	HST
Piston Pump Capacity (x2)	195 L/m
Relief Valve Piston Pump	386 bar
Tandem Gear Pump Capacity	
Front Section (HST Drive)	75 L/m @ 34 bar
Rear Section (Aux Output)	95 L/m @ 172 bar
Optional Pump Drive	95 L/m @ 172 bar

PERFORMANCE	
Max. Carrying Capacity	8,165 kg
Travel Speed - 1st Gear	736 km/h
Travel Speed - 2nd Gear	25.5 km/h
Gradability (unloaded)	32%
Turning Radius	3 m
Ground Pressure (full capacity)	.34 kg/c <sup>2</sup>

BROUGHT TO YOU BY:



630-365-1649 | info@rigsourceinc.com  
www.rigsourceinc.com | www.terramac.com